

Package: garchx (via r-universe)

October 25, 2024

Type Package

Title Flexible and Robust GARCH-X Modelling

Version 1.5

Date 2022-09-13

Author Genaro Sucarrat [aut, cre]

Maintainer Genaro Sucarrat <gsucarrat@gmail.com>

Description Flexible and robust estimation and inference of generalised autoregressive conditional heteroscedasticity (GARCH) models with covariates ('X') based on the results by Francq and Thieu (2018) <[doi:10.1017/S0266466617000512](https://doi.org/10.1017/S0266466617000512)>. Coefficients can straightforwardly be set to zero by omission, and quasi maximum likelihood methods ensure estimates are generally consistent and inference valid, even when the standardised innovations are non-normal and/or dependent over time, see <<https://journal.r-project.org/archive/2021/RJ-2021-057/RJ-2021-057.pdf>> for an overview of the package.

License GPL (>= 2)

Depends R (>= 3.4.0), methods, zoo

Suggests tvgarch, lgarch

BugReports <https://github.com/gsucarrat/garchx/issues>

URL <https://www.sucarrat.net/>

Repository <https://gsucarrat.r-universe.dev>

RemoteUrl <https://github.com/gsucarrat/garchx>

RemoteRef HEAD

RemoteSha 303ff3103c5ff015d82301c522ec853cd278f5f9

Contents

garchx-package	2
coef.garchx	3
garchx	5
garchxAvar	8
garchxObjective	9
garchxSim	10
gdif	11
glag	12
refit	14
rmnorm	15
ttest0	16

Index	18
--------------	-----------

garchx-package	<i>Flexible and Robust GARCH-X Modelling</i>
----------------	----------------------------------------------

Description

Flexible and robust estimation and inference of GARCH(q,p,r)-X models, where q is the GARCH order, p is the ARCH order, r is the asymmetry or leverage order, and 'X' indicates that covariates can be included. Suitable subsets of the coefficients can be restricted to zero by omission, and Quasi Maximum Likelihood (QML) methods ensure estimates are generally consistent, even when the standardised innovations are non-normal and/or dependent.

Details

Package: garchx
 Type: Package
 Version: 1.5
 Date: 2022-09-13
 License: GPL-2

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

Maintainer: Genaro Sucarrat

See Also

[garchxSim](#), [coef](#), [fitted](#), [logLik](#), [print](#), [residuals](#), [vcov](#)

Examples

```
##simulate from a garch(1,1):
set.seed(123)
y <- garchxSim(1000)

##estimate garch(1,1) model:
mymod <- garchx(y)
mymod
```

coef.garchx

*Extraction functions for 'garchx' objects***Description**

Extraction functions for objects of class 'garchx'

Usage

```
## S3 method for class 'garchx'
coef(object, ...)
## S3 method for class 'garchx'
fitted(object, as.zoo = TRUE, ...)
## S3 method for class 'garchx'
logLik(object, ...)
## S3 method for class 'garchx'
nobs(object, ...)
## S3 method for class 'garchx'
predict(object, n.ahead = 10, newxreg = NULL,
         newindex = NULL, n.sim = NULL, verbose = FALSE, ...)
## S3 method for class 'garchx'
print(x, ...)
## S3 method for class 'garchx'
quantile(x, probs=0.025, names = TRUE, type = 7, as.zoo = TRUE, ...)
## S3 method for class 'garchx'
residuals(object, as.zoo = TRUE, ...)
## S3 method for class 'garchx'
toLatex(object, digits = 4, ...)
## S3 method for class 'garchx'
vcov(object, vcov.type = NULL, ...)
```

Arguments

object	an object of class 'garchx'
x	an object of class 'garchx'
as.zoo	logical. If TRUE, then the returned result is of class zoo

n.ahead	integer that determines how many steps ahead predictions should be generated
newxreg	vector or matrix with the out-of-sample regressor values
newindex	zoo-index for the out-of-sample predictions. If NULL (default), then 1:n.ahead is used
n.sim	NULL or an integer, the number of simulations
verbose	logical. If TRUE, then the simulations - in addition to the predictions - are returned
probs	vector of probabilities
names	logical, whether to return names or not
type	integer that determines the algorithm used to compute the quantile, see quantile
digits	integer, the number of digits in the printed LaTeX code
vcov.type	NULL or a character that is (partially) matched to "ordinary" or "robust". The robust coefficient-covariance is that of Francq and Thieu (2018).
...	additional arguments

Value

coef:	numeric vector containing parameter estimates
fitted:	fitted conditional variance
logLik:	log-likelihood (normal density)
nobs:	the number of observations used in the estimation
predict:	a vector with the predictions (verbose=FALSE), or a matrix with both the predictions and the simulations (verbose=TRUE)
print:	print of the estimation results
quantile:	the fitted quantiles, i.e. the conditional standard deviation times the empirical quantile of the standardised innovations
residuals:	standardised residuals
vcov:	coefficient variance-covariance matrix

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Christian Francq and Le Quien Thieu (2018): 'QML inference for volatility models with covariates', *Econometric Theory*, doi:10.1017/S0266466617000512

See Also

[garchx](#), [garchxSim](#), [zoo](#)

Examples

```

##simulate from a garch(1,1):
set.seed(123)
y <- garchxSim(1000)

##estimate garch(1,1) model:
mymod <- garchx(y)

##print estimation results:
print(mymod)

##extract coefficients:
coef(mymod)

##extract and store conditional variances:
sigma2hat <- fitted(mymod)

##extract log-likelihood:
logLik(mymod)

##extract and store standardised residuals:
etahat <- residuals(mymod)

##extract coefficient variance-covariance matrix:
vcov(mymod)

##generate predictions:
predict(mymod)

```

garchx

*Estimate a GARCH-X model***Description**

Quasi Maximum Likelihood (ML) estimation of a GARCH(q,p,r)-X model, where q is the GARCH order, p is the ARCH order, r is the asymmetry (or leverage) order and 'X' indicates that covariates can be included. Note that the underlying estimation theory assumes the covariates are stochastic. The estimation procedure will, in general, provide consistent estimates when the standardised innovations are not normal or independent (or both), see Francq and Thieu (2018).

Usage

```

garchx(y, order = c(1,1), arch = NULL, garch = NULL, asym = NULL,
       xreg = NULL, vcov.type = c("ordinary", "robust"),
       initial.values = NULL, backcast.values = NULL, lower = 0,
       upper = +Inf, control = list(), hessian.control = list(),
       solve.tol = .Machine$double.eps, estimate = TRUE, c.code = TRUE,
       penalty.value = NULL, sigma2.min = .Machine$double.eps,
       objective.fun = 1, turbo = FALSE)

```

Arguments

<code>y</code>	numeric vector, time-series or zoo object. Missing values in the beginning and at the end of the series is allowed, as they are removed with the na.trim command
<code>order</code>	integer vector of length 1, 2 or 3, for example <code>c(1, 1, 1)</code> . The first entry controls the GARCH order, the second the ARCH order and the third the ASYM (asymmetry/leverage) order
<code>arch</code>	NULL or numeric vector containing the ARCH-terms to include. Note: If not NULL, then the value of the ARCH argument overrides the value of the first entry in the <code>order</code> argument
<code>garch</code>	NULL or numeric vector containing the GARCH-terms to include. Note: If not NULL, then the value of the GARCH argument overrides the value of the second entry in the <code>order</code> argument
<code>asym</code>	NULL or numeric vector containing the ASYM-terms (asymmetry/leverage terms) to include. Note: If not NULL, then the value of the ASYM argument overrides the value of the third entry in the <code>order</code> argument
<code>xreg</code>	numeric vector, time-series or zoo object. Missing values in the beginning and at the end of the series is allowed, as they are removed with the na.trim command
<code>vcov.type</code>	character, either "ordinary" or "robust", see vcov.garchx
<code>initial.values</code>	NULL or a numeric vector with the initial parameter values passed on to the optimisation routine, nlminb . If NULL, the default, then the values are chosen automatically
<code>backcast.values</code>	NULL or a non-negative numeric. The backcast value is used to initiate the forward recursion of the conditional variance. If NULL (default), then the value is chosen automatically (currently the average of y squared is used). If <code>backcast.values</code> is a non-negative numeric, then the initial recursion values are all set to this value
<code>lower</code>	numeric vector, either of length 1 or the number of parameters to be estimated, see nlminb
<code>upper</code>	numeric vector, either of length 1 or the number of parameters to be estimated, see nlminb
<code>control</code>	a list passed on to the <code>control</code> argument of nlminb
<code>hessian.control</code>	a list passed on to the <code>control</code> argument of optimHess
<code>solve.tol</code>	numeric value passed on to the <code>tol</code> argument of solve , which is called whenever the coefficient variance-coariance matrix is computed. The value controls the tolerance for detecting linear dependence between columns when inverting a matrix
<code>estimate</code>	logical, if TRUE then estimation is carried out. If FALSE, then the <code>initial.values</code> are used
<code>c.code</code>	logical, if TRUE then compiled C code is used in the forward recursion
<code>penalty.value</code>	NULL (default) or a numeric value. If NULL, then the log-likelihood value associated with the initial values is used. Sometimes estimation can result in NA and/or +/-Inf values. The <code>penalty.value</code> is the value returned by the objective function garchxObjective in the presence of NA or +/-Inf values

<code>sigma2.min</code>	numeric with default <code>.Machine\$double.eps</code> . To avoid taking taking the log of a very small value when computing the log-likelihood, <code>sigma2.min</code> is used as the lower bound of the fitted conditional variances, see the code of garchxObjective
<code>objective.fun</code>	numeric, either 1 or 0
<code>turbo</code>	logical. If FALSE (default), then the coefficient variance-covariance is computed during estimation, and the fitted values and residuals are attached to the returned object. If TRUE, then these operations are skipped, and hence estimation is faster. Note, however, that if <code>turbo</code> is set to TRUE, then the coefficient-covariance, fitted values and residuals can still be extracted subsequent to estimation with vcov.garchx , fitted.garchx and residuals.garchx , respectively

Value

A list of class 'garchx'

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Christian Francq and Le Quien Thieu (2018): 'QML inference for volatility models with covariates', *Econometric Theory*, doi:10.1017/S0266466617000512
Christian Francq and Jean-Michel Zakoian (2019): 'GARCH Models', 2nd Edition, Wiley

See Also

[garchxSim](#), [nlminb](#), [optimHess](#), [coef.garchx](#)

Examples

```
##simulate from a garch(1,1):
set.seed(123)
y <- garchxSim(1000)

##estimate garch(1,1) model:
mymod <- garchx(y)

##print estimation results:
print(mymod)

##extract coefficients:
coef(mymod)

##extract and store conditional variances:
sigma2hat <- fitted(mymod)

##extract log-likelihood:
logLik(mymod)

##extract and store standardised residuals:
```

```

etahat <- residuals(mymod)

##extract variance-covariance matrix:
vcov(mymod)

##generate predictions:
predict(mymod)

```

garchxAvar

Asymptotic Coefficient Covariance

Description

Compute the asymptotic coefficient-covariance of a GARCH(q,p,r)-X model by simulation. Note that the principles of how to use the arch, garch, asym and xreg arguments are the same as those of [garchx](#)

Usage

```

garchxAvar(pars, arch = NULL, garch = NULL, asym = NULL,
  xreg = NULL, vcov.type = c("ordinary", "robust"),
  innovations = NULL, Eeta4 = NULL, n = 1e+06, objective.fun = 1,
  seed = NULL)

```

Arguments

pars	vector of parameters of length 1 or more. The first component contains the coefficient-value of the intercept, the next component(s) the ARCH-coefficient(s), and so on.
arch	NULL or integer vector with the lags of the ARCH-terms to include. Works in the same way as the arch argument in the garchx function
garch	NULL or integer vector with the lags of the GARCH-terms. Works in the same way as the garch argument in the garchx function
asym	NULL or integer vector with the lags of the asymmetry terms to include. Works in the same way as the asym argument in the garchx function
xreg	NULL, or a vector or matrix with the covariates of the model. Works in the same way as the xreg argument in the garchx function
vcov.type	character that determines the type of coefficient-covariance
innovations	NULL or a vector with the standardised innovations to use. If NULL, then the innovations are standard normal
Eeta4	numeric, the fourth moment of the innovations. If NULL, then the value is estimated internally. Note: The value of Eeta4 is only used if vcov.type = "ordinary", otherwise it is ignored
n	integer, the number of observations to use in the simulations

objective.fun	integer equal to 1 or 0 that determines the type of objective function to use, see the code of garchxObjective
seed	NULL or an integer that sets the seed (the value is passed on to set.seed . Useful for reproducibility)

Value

A matrix

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Christian Francq and Le Quien Thieu (2018): 'QML inference for volatility models with covariates', *Econometric Theory*, doi:10.1017/S0266466617000512
Christian Francq and Jean-Michel Zakoian (2019): 'GARCH Models', 2nd Edition, Wiley

See Also

[garchx](#), [garchxSim](#), [vcov.garchx](#)

Examples

```
##asymptotic coefficient-covariance of a garch(1,1)
##note: the estimate is rough, since n is small
intercept <- 0.2
alpha <- 0.1
beta <- 0.8
pars <- c(intercept, alpha, beta)
seed <- 123 #for reproducibility
garchxAvar(pars, arch=1, garch=1, n=10000, seed=seed)
```

garchxObjective

Auxiliary functions

Description

Auxiliary functions used in estimation. Not intended for the average user

Usage

```
garchxObjective(pars, aux)
garchxRecursion(pars, aux)
```

Arguments

pars numeric vector of parameters
 aux [list](#) created by [garchx](#)

Value

garchxObjective: value of the objective function
 garchxRecursion: fitted conditional variance

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

See Also

[garchx](#), [fitted.garchx](#), [residuals.garchx](#)

garchxSim *Simulate from a GARCH-X model*

Description

Simulate from a GARCH(q,p,r)-X model. Optionally, if verbose=TRUE, the conditional variance and innovations are also returned.

Usage

```
garchxSim(n, intercept = 0.2, arch = 0.1, garch = 0.8, asym = NULL, xreg = NULL,
  innovations = NULL, backcast.values = list(), verbose = FALSE, as.zoo = TRUE,
  c.code = TRUE)
```

Arguments

n integer
 intercept numeric
 arch NULL or numeric vector with the values of the ARCH-coefficients
 garch NULL or numeric vector with the values of the GARCH-coefficients
 asym NULL or numeric vector with the values of the asymmetry-coefficients
 xreg NULL or numeric vector with the values of the X-term
 innovations NULL or numeric vector with the innovations. If NULL, then standard normal innovations are generated with [rnorm](#)
 backcast.values [list](#) with backcast values

verbose	logical
as.zoo	logical. If TRUE (default), then the returned object is of class <code>zoo</code>
c.code	logical. If TRUE (default), then compiled C code is used for the recursion (faster). Otherwise R code is used (slower)

Value

a numeric vector or matrix with the simulated values.

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

See Also

[garchx](#), [zoo](#)

Examples

```
##simulate from a garch(1,1):
y <- garchxSim(1000)

##simulate from a garch(1,1) with asymmetry/leverage:
yy <- garchxSim(1000, asym=0.1)

##simulate from a garch(1,1) w/user-provided backcast values:
yyy <- garchxSim(1000, backcast.values=list(z2=1, sigma2=0.5))
```

gdiff

Difference a vector or a matrix, with special treatment of zoo objects

Description

Similar to the `diff` function from the base package, but `gdiff` enables padding (e.g. NAs or 0s) of the lost entries. Contrary to the `diff` function in the base package, however, the default in `gdiff` is to pad (with NAs). The `gdiff` function is particularly suited for `zoo` objects, since their indexing is retained

Usage

```
gdiff(x, lag = 1, pad = TRUE, pad.value = NA)
```

Arguments

x	a numeric vector or matrix
lag	integer equal to the difference-length (the default is 1)
pad	logical. If TRUE (default), then the lost entries are padded with <code>pad.value</code> . If FALSE, then no padding is undertaken
pad.value	numeric, the pad-value

Value

A vector or matrix with the differenced values

Note

Empty

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

See Also

[diff](#), [glag](#), [lag](#)

Examples

```
##1st difference of a series:
x <- rnorm(5)
gdiff(x)

##1st difference with no padding:
gdiff(x, pad=FALSE)

##1st difference retaining the original zoo-index ordering:
gdiff(as.zoo(x))

##1st difference of a matrix:
y <- matrix(rnorm(8),4,2)
gdiff(y)

##2nd difference of the same matrix:
gdiff(y, lag=2)
```

glag

Lag a vector or a matrix, with special treatment of zoo objects

Description

Similar to the [lag](#) function from the stats package, but [glag](#) enables padding (e.g. NAs or 0s) of the lost entries. Contrary to the [lag](#) function in the stats package, however, the default in [glag](#) is to pad (with NAs). The [glag](#) is particularly suited for [zoo](#) objects, since their indexing is retained

Usage

```
glag(x, k = 1, pad = TRUE, pad.value = NA)
```

Arguments

x	a numeric vector or matrix
k	integer equal to the lag (the default is 1)
pad	logical. If TRUE (default), then the lost entries are padded with pad.value. If FALSE, then no padding is undertaken
pad.value	the pad-value

Value

A vector or matrix with the lagged values

Note

Empty

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

See Also

[lag](#), [gdiff](#), [diff](#)

Examples

```
##lag series with NA for the missing entries:
x <- rnorm(5)
glag(x)

##lag series with no padding:
x <- rnorm(5)
glag(x, pad=FALSE)

##lag series and retain the original zoo-index ordering:
x <- as.zoo(rnorm(5))
glag(x)

##lag two periods:
glag(x, k=2)
```

refit	<i>Refit a model to new data</i>
-------	----------------------------------

Description

Refit a model to new data, typically for cross-validation purposes. Re-estimation (reestimate) is optional (the default is FALSE).

Usage

```
##generic:
refit(object, ...)

##S3 method for 'garchx' objects:
## S3 method for class 'garchx'
refit(object, newy = NULL, newxreg = NULL,
      backcast.value = NULL, reestimate = FALSE, ...)
```

Arguments

object	an object of class garchx
newy	vector, the new 'y' data, see garchx
newxreg	the new 'xreg' data, if any, see garchx
backcast.value	NULL or a non-negative numeric, see garchx
reestimate	logical. If FALSE (default), then the estimates from object are used on the new data. If TRUE, then the model is re-estimated using the new data
...	further arguments passed to or from other methods

Details

`refit.garchx` is a convenience function to facilitate cross-validation and related analyses.

Value

A list of class 'garchx'

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

See Also

[garchx](#)

Examples

```
##simulate from a garch(1,1):
set.seed(123)
y <- garchxSim(1000)

##estimate garch(1,1) model:
mymod <- garchx(y)

##new data (e.g. 'out-of-sample' or 'test' data):
yy <- garchxSim(100)

##apply the estimates of 'mymod' on yy data:
refit(mymod, newy=yy)
```

rmnorm

Random number generation from the multivariate normal distribution

Description

This function is a speed-optimised version of the `rmnorm` function from the `mnormt` package of Adelchi Azzalini (2013).

Usage

```
rmnorm(n, mean = NULL, vcov = 1)
```

Arguments

<code>n</code>	integer, the number of observations to generate
<code>mean</code>	numeric vector, i.e. the mean values
<code>vcov</code>	numeric matrix, i.e. the variance-covariance matrix

Value

A matrix of `n` rows

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Adelchi Azzalini (2013): 'mnormt: The multivariate normal and t distributions', R package version 1.4-7, <https://CRAN.R-project.org/package=mnormt>

Examples

```
##generate from univariate standardised normal:
z1 <- rmnorm(100)

##generate from bivariate, independent standardised normal:
z2 <- rmnorm(100, vcov=diag(c(1,1)))

##generate from bivariate, dependent standardised normal:
z3 <- rmnorm(100, vcov=cbind(c(1,0.3),c(0.3,1)))
```

ttest0

T-tests and Wald-tests under nullity

Description

The permissible parameter-space of GARCH-models is bounded from below by 0. This means non-standard inference is required when one or more parameters are 0 under the null hypothesis, a frequent situation in empirical applications. The functions `ttest0` and `waldtest0` perform t-tests and Wald-tests when one or more parameters is 0. In the latter test, the Wald-test, the critical values are obtained by simulation, see Francq and Thieu (2018).

Usage

```
ttest0(x, k = NULL)
waldtest0(x, r = 0, R = NULL, level = c(0.1,0.05,0.01),
          vcov.type = NULL, quantile.type = 7, n = 20000)
```

Arguments

<code>x</code>	an object of class 'garchx'
<code>k</code>	NULL (default) or a vector of integers with the coefficients to test. If NULL, then all coefficients apart from the intercepts are tested
<code>r</code>	vector with restrictions
<code>R</code>	NULL (default) or a full-rank matrix. If NULL, then R is specified such that a test of all coefficients - apart from the intercept - is equal to the restriction <code>r</code> . If <code>length(r)==1</code> , then it is recycled so that its dimension match that of R
<code>level</code>	vector of significance levels whose critical values should be computed
<code>vcov.type</code>	NULL or a character that determines the type of coefficient-covariance to use, see vcov.garchx
<code>quantile.type</code>	integer, the algorithm used to compute the quantile, see quantile
<code>n</code>	integer, the numer of simulations used to estimate the critical values

Details

The `ttest0` function performs a t-test of coefficient k with 0 as null. Under this null the parameter is on the boundary of the admissible parameter space, and so the distribution is non-standard under the null. The function `ttest0` returns the result(s) of these non-standard t-test(s), see Francq and Thieu (2018). If $k=$ NULL, the default, then a test for each coefficient apart from the intercept is undertaken.

The `waldtest0` function performs a Wald-test of the restrictions in r , when one or more of its elements are 0, see Francq and Thieu (2018).

Value

`ttest0`: a matrix with the t-tests
`waldtest0`: a list with the test-statistic and the critical values

Author(s)

Genaro Sucarrat, <http://www.sucarrat.net/>

References

Christian Francq and Le Quien Thieu (2018): 'QML inference for volatility models with covariates', *Econometric Theory*, doi:10.1017/S0266466617000512

See Also

[garchx](#), [quantile](#), [vcov.garchx](#), [rmnorm](#)

Examples

```
##simulate and estimate a garch(1,1):
set.seed(123)
y <- garchxSim(1000)
mymod <- garchx(y)

##t-tests:
ttest0(mymod)

##wald-test:
waldtest0(mymod)
```

Index

* Econometrics

- coef.garchx, 3
- garchx, 5
- garchx-package, 2
- garchxAvar, 8
- garchxObjective, 9
- garchxSim, 10
- gdiff, 11
- glag, 12
- refit, 14
- rmnorm, 15
- ttest0, 16

* Financial Econometrics

- coef.garchx, 3
- garchx, 5
- garchx-package, 2
- garchxAvar, 8
- garchxObjective, 9
- garchxSim, 10
- gdiff, 11
- glag, 12
- refit, 14
- rmnorm, 15
- ttest0, 16

* Statistical Models

- coef.garchx, 3
- garchx, 5
- garchx-package, 2
- garchxAvar, 8
- garchxObjective, 9
- garchxSim, 10
- gdiff, 11
- glag, 12
- refit, 14
- rmnorm, 15
- ttest0, 16

* Time Series

- coef.garchx, 3
- garchx, 5

- garchx-package, 2
- garchxAvar, 8
- garchxObjective, 9
- garchxSim, 10
- gdiff, 11
- glag, 12
- refit, 14
- rmnorm, 15
- ttest0, 16

- coef, 2
- coef.garchx, 3, 7

- diff, 11–13

- fitted, 2
- fitted.garchx, 7, 10
- fitted.garchx (coef.garchx), 3

- garchx, 4, 5, 8–11, 14, 17
- garchx-package, 2
- garchxAvar, 8
- garchxObjective, 6, 7, 9, 9
- garchxRecursion (garchxObjective), 9
- garchxSim, 2, 4, 7, 9, 10
- gdiff, 11, 13
- glag, 12, 12

- lag, 12, 13
- list, 6, 10
- logLik, 2
- logLik.garchx (coef.garchx), 3

- na.trim, 6
- nlminb, 6, 7
- nobs.garchx (coef.garchx), 3

- optimHess, 6, 7

- predict.garchx (coef.garchx), 3
- print, 2

print.garchx (coef.garchx), 3

quantile, 4, 16, 17

quantile.garchx (coef.garchx), 3

refit, 14

residuals, 2

residuals.garchx, 7, 10

residuals.garchx (coef.garchx), 3

rmnorm, 15, 15, 17

rnorm, 10

set.seed, 9

solve, 6

toLatex.garchx (coef.garchx), 3

ttest0, 16

vcov, 2

vcov.garchx, 6, 7, 9, 16, 17

vcov.garchx (coef.garchx), 3

waldtest0 (ttest0), 16

zoo, 3, 4, 6, 11, 12